WANG, C., HOU, J., MILLER, D., BROWN, I. and JIANG, Y. 2019. Flood risk management in sponge cities: the role of integrated simulation and 3D visualization. *International journal of disaster risk reduction* [online], 39, article ID 101139. Available from: <u>https://doi.org/10.1016/j.ijdrr.2019.101139</u>

Flood risk management in sponge cities: the role of integrated simulation and 3D visualization.

WANG, C., HOU, J., MILLER, D., BROWN, I., JIANG, Y.

2019.



This document was downloaded from https://openair.rgu.ac.uk



Flood Risk Management in Sponge Cities: The Role of Integrated Simulation and 3D Visualization

3 Chen Wang ^{1, 2, *}, Jingming Hou ^{1, *}, David Miller ², Iain Brown ³ and Yang Jiang ⁴

4 ¹ State Key Laboratory of Eco-hydraulics in Northwest Arid Region, Xi'an University of Technology, Xi'an, 710048,

5 China

- 6 ² The James Hutton Institute, Craigiebuckler, Aberdeen, UK. AB15 8QH
- ³ School of Social Sciences, University of Dundee, Dundee, UK. DD1 4HN
- 8 ⁴ School of Computing Science and Digital Media, Robert Gordon University, UK. AB10 7QB
- 9 * Correspondence: chen.wang@hutton.ac.uk; jingming.hou@xaut.edu.cn
- 10 Tel: +44-344-928-5428; Tel: +86 (0)29 82312685

11 **Abstract:** The Sponge City concept has been promoted as a major programme of work to address increasing 12 flood risk in urban areas, in combination with wider benefits for water resources and urban renewal. However, 13 realization of the concept requires collaborative engagement with a wide range of professionals and with 14 affected communities. Visualization can play an important role in this process. In this research, a sponge city 15 flood simulation and forecasting system has been built which combines hydrological data, topographic data, 16 GIS data and hydrodynamic models in real-time and interactive display in a three-dimensional environment. 17 Actual and design flood events in a pilot sponge city have been simulated. The validation results show that the 18 simulated urban water accumulation process is consistent with the actual monitoring data. Use of advanced 19 virtual reality technology can enable simulations to be placed in the wider design context including enhanced 20 awareness of multiple functions of urban ecosystems. This procedure can therefore reduce the information 21 communication gap and encourage innovation regarding low impact development required for sponge city 22 construction.

23 Keywords: Sponge City; Flood Risk Management; 3D Visualization; GIS; Low impact development

24

25 1. Introduction

During recent decades, China has undergone a major and unprecedented urbanization that has been unparalleled in global terms. This transition has brought significant environmental challenges, including for water resources and flood risk management, for which more sustainable outcomes are now being sought. In terms of disaster risk, unconstrained urbanization can significantly increase both exposure and vulnerability to natural hazards, especially for fast-onset extreme events such as flooding through modification of hydrological pathways due to soil sealing and use of impermeable surfaces. This risk is likely to be further exacerbated by
 changes in the intensity and magnitude of extreme events due to climate change.

33 In December 2013, President Xi Jinping announced a national plan to reduce flooding in China's cities, as 34 a response to the increased frequency of serious urban flooding in the country. The main aim was to transform 35 current urban areas into "sponge cities" by upgrading the existing urban drainage infrastructure and utilising 36 natural systems to improve water retention, infiltration and drainage. "Sponge City" is a new concept of 37 integrated urban stormwater management, which enables Chinese cities to have good resilience in adapting to 38 environmental changes and coping with natural disasters [1]. The sponge city concept includes water bodies 39 such as rivers, lakes and ponds, as well as supporting urban facilities such as green spaces, gardens and 40 permeable road surfaces. Rainwater is infiltrated, purified, stored and reused, with residual flows routed 41 through a network of pipes and pumping stations, to effectively raise the design standard of urban drainage 42 system and reduce the flood risk in the city. Currently, there are 30 pilot cities in China with specific 43 water-related targets on facilitating natural pathways for interception, infiltration and purification in sponge 44 cities. The aim of the programme has now also been extended to incorporate a wider range of multiple benefits 45 in addition to flood risk management, and to include planning for climate change.

46 The sponge city initiative was inspired by low impact developments (LID) elsewhere in the world that 47 would be scaled and transferred into the Chinese urban context. These existing developments include LID in the 48 US [2], water sensitive urban design (WSUD) in Australia[3], sustainable urban drainage systems (SUDS) in 49 the UK[4], and integrated urban water management systems in Denmark and Sweden[5][6]. For example, in 50 Malmö, different storm-water collection networks as well as large-scale open storm-water handling 51 implementations are already present in forms such as ponds, wetlands, swales, canals, detention lakes, and 52 green roofs[5]. Copenhagen is mainly dominated by fully developed sewer systems[6] but recent extreme 53 events have shown a need to redesign the drainage system to better adapt to extreme rainfalls; this goal is being 54 achieved through modifications to the connectivity of the combined sewer network and integrated use of low 55 sensitivity surfaces coinciding with public spaces (e.g. parks, sport fields and open space for temporary storage 56 of storm water)[5].

57 There are numerous major challenges for sponge city development with regarding to technical/physical, 58 legal/regulatory, financial, and community/institutional engagement at the local, regional and national 59 levels[7]. A focus only upon the technical challenge is therefore insufficient to deliver the ultimate objectives, 60 requiring design standards and code to be aligned with monitoring/evaluation, education/training and effective 61 operation/maintenance. At the core of the concept is the enhanced use of natural infrastructure through 62 eco-engineering in local planning, regulations and projects to help reduce flood exposure. However, 63 eco-engineering approaches for risk reduction represent a step change from conventional engineering 64 techniques and their successful application requires integration of science, design and policy based upon agreed 65 decision outcomes[8]. Hence, although progress in sustainable urban water management is influenced by 66 technological innovations, a key challenge has been identified in aligning sponge city initiative projects with 67 infrastructure and urban renovation portfolios[9]. Consequently, the major investment in sponge city 68 construction programmes requires equivalent emphasis on stakeholder engagement and public perception in 69 order to incorporate community opinions on current construction plan and future flood risk management. 70 Researchers have therefore highlighted important knowledge gaps in current initiatives including requirements 71 for improved inter-disciplinary approaches, a comprehensive design framework, and improved application of 72 information technology [10].

73 The scale of ambition and the challenges involved in converting a visionary concept into a practical reality 74 suggest there is a valuable role for visualization in the Sponge Cities programme. This is further emphasized by 75 the additional complications involved when implementing the concept into specific local contexts, each with 76 their distinctive biophysical and socioeconomic features. Traditional landscape architecture visuals are often 77 employed to convey key aspects of the sponge city concept (e.g. permeable surfaces and associated greenspace) 78 but these do not facilitate an interactive or immersive engagement with the proposed design features. In other 79 contexts, innovative use of computer-based visualization and Virtual Reality (VR) technology has been shown 80 to encourage greater engagement and awareness of landscape design challenges amongst diverse 81 participants[11][12], further highlighting our rationale for investigating its application in meeting the design 82 challenges of sponge cities. Most notably, the additional realism of a 3D application may also help avoid 83 misunderstandings that occur between the design teams and stakeholders when using 2D illustrations that 84 typically leads to the need for re-design and reworking during the design phase.

85 In flood risk management, the main bottleneck to risk reduction is usually not the lack of information, but 86 rather how this information is communicated and perceived[13]. 3D visualization and associated tools can 87 therefore have benefits which could support delivery of the types of aspirations or regulatory requirements in 88 public policies which relate to planning and development. Furthermore, an important requirement in advancing 89 good design practice is understanding how sponge cities function during extreme events and not just in normal 90 conditions. This functioning not only refers to the storage of water for flood risk reduction but also associated 91 implications for the wider range of benefits that the design might provide, extending also to the visual and 92 aesthetic aspects which may also be perceived as crucially important by local people and stakeholders (e.g.

93 businesses)[14]. This identifies the further advantages of combining visualization with simulation modelling to 94 explore the expected changes during a particular event, such as a design flood event. Following this rationale, a 95 combined simulation-visualization platform can become an important shared learning tool, meaning planner, 96 decision maker and public can get involved in developing a shared vision for the sponge city concept in a 97 collaborative format.

98 2. Flood Simulation

99

100 Flood simulation and modelling can be used to provide relevant information on the dynamics of flood risk 101 at a location and therefore the consequences for people living there. Simulating and modelling flood hazard are 102 rapidly developing fields in hydrology[15]. Topographic data are crucial for flood inundation modelling and it 103 is best to use recent and highly accurate topographic data. Current methods of flood hazard warning include 104 numerical simulation[16][17][18][19], remote sensing approaches[20][21], rainfall data estimation[22] and 105 flood simulation based on geographic information system (GIS) [23][24]. Although these methods can solve 106 some important problems, there are still two disadvantages in terms of risk communication: i) the flood 107 prevention system is constructed in 2D environments other than 3D real world; ii) flood risk forecasts are 108 mainly based on the analysis of historical data.

109 There are increasing requirements for developing efficient flood warning systems for decision making and 110 risk management. Flood warning systems must be reliable and designed to operate during the most severe 111 floods. A web-based flood forecasting system can be used to carry out real-time rainfall data conversion, 112 model-driven hydrologic forecasting, model calibration, precipitation forecasting, and flood analysis [25]. 113 However, the effectiveness of this system can be compromised by deficiencies of hydraulic flood spreading 114 procedures as the extreme event progresses [26]. Remotely sensed precipitation data and hydrologic modelling 115 are used to monitor flooding in regions that regularly experience extreme precipitation and flood events[27], but 116 this needs an offline process for data collection and also appears less efficient for real time implementation. The 117 ability of high-resolution TerraSAR-X synthetic aperture radar (SAR) data to detect flooded regions in urban 118 areas with a semiautomatic algorithm for the detection of floodwater in urban areas has been validated using 119 aerial photographs[28], but the main drawback of this approach is its poor display performance due to its 2D 120 processing. A European flood forecasting system has been developed for determining what flood forecast skill 121 can be achieved for given basins, meteorological events and prediction products[29]. It consists of several 122 components: i) global numerical weather prediction models; ii) regional numerical weather prediction model; 123 iii) a catchment hydrology model; iv) flood inundation model. The major challenge of this approach is dealing 124 with uncertainty in such a complex system of linked numerical codes and database, and challenges have been identified in applying such a system in developing countries with limited historical data [26], especially in
locations where flood vulnerability is an increasing concern [30].

127 The present study aims to show how a combined simulation-visualization approach can enhance decision 128 support by incorporating model uncertainty analysis, computationally efficient real-time data 129 assimilation/forecasting algorithms, 2D inundation modelling[31], and 3D data visualization[32]. Previous 130 work has shown that this requires a consistent approach to data integration and model development across the 131 suite of tools and techniques [33]. In [34], an early flood warning system has been developed which is useful to 132 provide timely and correct information for flash flood conditions and to facilitate anticipatory adaptation 133 actions to reduce risks, including to both reduce risk exposure and vulnerability. It combines offline hydrologic 134 analysis and online flood alert application. Hydrologic simulation was performed using HEC-HMS for runoff 135 forecasting with a client-server programme used to visualize the real time flood condition and to deliver the 136 early warning message.

137 3. Case Study of Xixian new area138



139

140 **Fig.1.** Pilot area location: Fengxi new town in Xixian new area of China

141

142 Xixian new area is China's seventh state-level new area and included in the first batch of national sponge

143 city construction pilot cities[35]. There are five new towns in Xixian new area which covers 882 km². The

current population is 0.96 million and planned to be 2.36 million by 2020. The pilot area of sponge city

145 construction in Xixian new area is the core area of Fengxi new town. It starts from the Xibao highway in the 146 south, to the Tongyi road in the north, to the Wei River in the west, and to Hanfei Road in the east, with a total 147 area of 22.5 km². The locations of the pilot and core area are shown in Fig.1.

The main goal of the plan is to design compact, ecologically-based, low carbon, and harmonious garden city including forest protection system, country parks, mitigation of heat island effect, public health facilities and social welfare system. The sponge city programme in Xixian new area is designed to utilize natural systems (e.g. rain garden, green roof, permeable pavement, underground storage tank) to improve urban ecosystem functions and reduce urban flooding.

The construction of Sponge City consists of LID technology, drainage system and excessive rainwater retention system. The Sponge City plan aims to co-ordinate and integrate these three major design systems through three main types of LID in the Xixian new area: bioretention, permeable/porous pavement system and green roof or ecological roof (Ecoroof).

157 According to the design characteristics of roads in Xixian new area, the LID measures along both sides of 158 the pilot area are mainly rainwater gardens and ecologically-integrated vegetated ditch. The test site in Xixian 159 has implemented permeable paving on the sidewalks of the Qinhuang Road and the Kang-ding-he-yuan 160 residential area. The hydrological role of Permeable/Porous Pavement System (PPS) is to enhance the 161 infiltration of rainwater, reduce impervious area, and to improve water quality through interception and reduced 162 runoff of pollutants. Green roof is also very important to LID by using vegetated roofs to intercept rainwater, 163 and at the same time achieving other energy saving functions, such as reducing the heat island effect and 164 lowering the city temperature through evapotranspiration processes. Xixian new area has adopted a green roof 165 design in the western cloud valley.

166 4. Methodology

167

144

unouongy

The framework used for the development of a 3D model and simulation of design and actual flood in pilot sponge city brings together the design of LID (e.g. green roof and rain garden), compilation into a model of the site, design and representation of 2D flood events within an immersive 3D environment, implementation as tools for flood risk management, and user involvement in stakeholder workshop (Fig.2).

- 172
- 173
- 174
- 175



Fig.2. Framework for the development of the 3D model and simulation of design and actual flood in pilot sponge city with LID scenarios.

191 The tools used in the development and implementation of the 3D model were PC-based, enabling the 192 incorporation of interactive functionality for manipulating features in such models. Inputs comprise spatial data 193 and associated imagery, simulated flood data layers, and 3D virtual components. The main part of the system 194 consists of Fengxi new town visualization with five interactive modules, featuring LID scenarios in VR 195 environment. The model is then exported into a viewer (Octaga) in which the functionality is coded in 196 JavaScript. The VR experience is used to communicate flood risk and therefore provides a collaborative 197 platform to enhance flood resilience and understand co-benefits from sponge city design features.

4.1 Urban Flood Simulation Model

190

200 The numerical model that integrates hydrological and hydrodynamic processes has been developed to 201 simulate the rain and flood process in the study area. This model uses the Godunov-type finite volume method 202 and applies the second-order algorithm of the second-order MUSCL (Monotonic Upwind Scheme for 203 Conservation Laws) method to strictly maintain the conservation of matter and robustly solve the discontinuity 204 problem[36]. Water and momentum flux are calculated by the Harten-Lax-van Leer-contact (HLLC) 205 approximate Riemann solver with the contact wave restored [37]. The bottom slope source term is processed by 206 previous proposed flux method applied to a complex grid[38]. The friction resistance is calculated using a 207 semi-implicit method with good stability, and the time is advanced using the two-step Runge-Kuta methods[39]. The use of GPU (Graphics Processing Unit) parallel computing technology to accelerate the calculation process can achieve large-scale computing on a single machine[40]. The model has high accuracy and computational efficiency, and is suitable for large-scale and complex urban storm-water process simulations. It has been previously validated [40] by a comparative analysis of simulated and measured data from a small watershed. The model used an open boundary during the simulation of urban storm floods. There was no accumulated water on the initial surface, and assuming soil saturation, the infiltration rate did not change over time, with the courant number (CFL) set to 0.5. The simulation was carried out for 5 hours. The accumulation of standing water in the study area under various design storm conditions was then obtained.

4.1.1 Flood Simulation and Model Validation

For the purpose of evaluating the computational efficiency and accuracy of the flood model, some typical residential districts in Xixian new area of Shanxi Province were selected as study sites, located between Xi'an and Xianyang City built-up areas (Fig.3(a)). The existing architectures are mainly residential buildings and school houses. The study area is located within a temperate continental monsoon climate zone. The average annual rainfall precipitation is about 520 mm, of which the precipitation from July to September accounts for about 50% of the annual rainfall, and the summer rainfall is mostly in the form of heavy rain, which has previously caused natural disasters such as urban floods. The model uses as input the measured rainfall and underlying surface data to simulate the urban pluvial flooding on the main street of the study area and compare it with the actual monitoring data to verify the model.





Duration /h 0 0.5 1 1.5 2 2.5 3 3.5 4 4.5 5 5.5 6 6.5 7 7.5 uE4 //ep6 gr 8

Fig.3. (a) Orthophoto map of the study area; (b) Digital elevation map of the study area; (c) Measured rainfall in 25th August 2016

246 The model input data is divided into four parts: rainfall data, topographic data, infiltration data, and land 247 use data. The observed rainfall data are provided by the weather station at No. 10 Building of Western cloud 248 valley in Xixian New Area on August 25, 2016. The rainfall was of the double-peak type with a peak rainfall 249 intensity at 3.1 hours, and lasted 7 hours, with a cumulative rainfall of 66 mm; the rainfall return period was a

250 one in 50-year event at this location. Specific model input parameters are shown in Fig.3 and Table 1.

251 Table 1 Underlay surface properties and Manning Coefficient

Land use Classification	Permeability	Manning Coefficient
Residential (16%)	80%	0.015
Traffic Land (32%)	0	0.014
Bare land (18%)	100%	0.03
Forest Land (17%)	100%	0.2
Grass Land (17%)	100%	0.06



Model calculations use open boundaries with no inflows around. The calculation process was performed 253 using the courant number (CFL) of 0.5 to simulate the water accumulation process from the beginning to 8 254 hours rainfall.

255 The simulation uses a microcomputer equipped with an NVIDIA GeForce GTX 1080 graphics card. The 256 single-precision floating-point (32-bit) computing capability is 9 TFlops/s. Since this video card is positioned as 257 a game card, the actual double-precision floating-point (64-bit) operation capability is less than 1/32 of the 258 single-precision operation capability, and the model calculation is shared at 45169 s (12.5 h). In order to solve 259 this problem, the model is also running on a computer equipped with a professional graphics card Tesla K20 260 with double-precision floating-point performance up to 1.17 TFlops/s. Fig.4(a) shows the process of water 261 accumulation in this simulation.





263

264

265
266

267

268

269

Fig.4. (a) Urban flood risk map for the study area; (b) Comparison between simulated water accumulation and measured water accumulation

In Fig.4(b), three inundation regions which are more severely affected by urban flood are marked and compared with the actual measurement records. From Fig.4(b) and Table 2, it can be seen that the location of the simulated water is consistent with the location of the urban pluvial flooding (three locations), and the degree of accumulated water at each point is similar to the measured data. The average relative error of the area of accumulated water is 3.44%. The average relative error of water depth within the reservoir is 16.49%. The comparison results show that the simulated urban water accumulation process is consistent with the actual monitoring process.

277 Table 2 Comparing simulated water level with actual situation

Location of waterlogging	Area of waterlogging /m ² (simulation result / actual measurement)	Water depth of inundation area /cm (simulation result / actual measurement)	
A. Baimahe Road North Section	1621.51 / >1600	55 / >50	
B.Tongyi Road East Section	464.21 / >480	35 / >30	
C. Tongyi Road West Section	1566.12 / >1600	40 / >40	

278

279

281 4.1.2 Design Rainstorm Event Simulation

Using rainfall data at Xianyang hydrological station from 1981 to 2016, the simulation model solved the

following rainstorm intensity equation of the "China Outdoor Drainage Design Code" (GB50014-2006) [41] for

284 Fengxi new town in Xixian new area.

$$q = \frac{1239.91 \times (1 + 1.971 \times \lg p)}{(t + 7.4246)^{0.8124}}$$
(1)

285

286 Where: q is the storm intensity (unit: $L/(s \cdot hm^2)$, p is the return period (unit: a), the current value range is

287 2a~200a; t is the rainfall duration (unit: min), with the value range between 1 to 1440 min.

Fig.5 shows the two hours design rainstorm rainfall with the return period of 50 years.



298 Fig.5. Two hours design rainstorm with the return period of 50 years

299

300 4.2 LID model and application in VR

301 *4.2.13D Model Creation*

302 Developing 3D Models is the initial step towards sponge city test site visualization. For this purpose, a 3D

303 model was created of the land area surrounding Fengxi new town as follows:

- 304 (i) Lidar Digital Terrain Model extracted for the land around Fengxi new town.
- 305 (ii) High-resolution aerial imagery used for background landscape textures.
- 306 (iii) Autodesk Infraworks used to render a 3D model for Fengxi new town new area test site.
- 307 (iv) Buildings were derived from Lidar point classification
- 308 Further elements added to the model were:
- 309 (i) Features associated with urban environments, developed in Autodesk Maya, Sketchup including
 310 transportation, woodland and pedestrian.
- 311 (ii) GIS data layers representing current land use in Fengxi new town test site.
- 312 (iii) Simulated flood data layers to distinguish between planned design without LID and containing LID.

314 4.2.2 Terrain data, texture map and parameters





317 **Fig.6.** Land Use Classification 318

319 To ensure the accuracy of the simulation, the digital terrain data of the study area is captured with a 320 resolution of 1m. Based on the orthophoto map, five types of land use (forest land, grassland, bare land, traffic 321 and residential land) in the study area are shown in Fig.6. The surface texture map is obtained from Unmanned 322 Aerial Vehicle (UAV) with a grid resolution of 6 cm. The Manning coefficient for each type of land use is 323 determined according to reference data in the literature[42]. The infiltration rate for bare land, grassland and 324 forest land is calculated based on actual measurement plus once a year drainage standard (LID not 325 implemented) and actual measurement plus once in three years drainage standard (LID implemented). The 326 infiltration rate for residential land and roads only rely on drainage system which is based on once in three years 327 or once a year drainage standard (LID implemented or not).

328 **Table 3** Land Use types, surface infiltration rate and manning coefficient

Land Use	Area	Percentage (%)	Manning Coefficient (n)	Infiltration rate (mm/h)	
Classification	(km ²)			Without LID	LID
Residential	0.2	28.09	0.015	10.47	77.7
Bare land	0.022	3.09	0.030	149.26	216.49
Grassland	0.19	26.69	0.060	55.5	127.77
Forest Land	0.21	29.49	0.200	120.86	188.09
Traffic Land	0.09	12.64	0.014	10.47	77.7

- According to the Fengxi new town rainstorm formula, when the rainfall intensity is greater than 10.74 mm/h, soil infiltration and the pipe network will be unable to remove all surface water and it will accumulate and cause surface runoff. The parameters taken for each land use type are shown in Table 3.
- 333 4.2.3 User Interaction Features

334 The user interaction interface has been developed to fit with the content and output of 3D model to be 335 consistent with the purpose of use (Fig.7). It includes 3D icons 'drag-and-drop' module, design analysis 336 module, 3D stereo panorama module, storyboards module and online shared view module. This part of the 337 experiment focused on the interaction and usability of the interface, and the recognizability of the type of 338 visualization. The 3D icons 'drag-and-drop' module allows participants to choose where they would like to 339 position elements (trees, cars, characters, etc.). The 2D and 3D inundated area can be measured in the design 340 analysis module. '3D stereo panorama' module shares the VR experience as the weblink or QR code which 341 provides 360° view of rendered panorama. Through the 'storyboards' module, a user will be guided on a 342 prepared tour of specified features including a series of snapshot views or a dynamic, video pathway through 343 parts of our sponge city 3D model. Online shared view module is also used to capture user/stakeholder 344 comments of sponge city design plans.



- 345 346
 - **Fig.7.** User Interaction Features applied in Sponge City Design Plans
- 347
- 348 4.2.4 Stakeholder Workshop

349 Developed models are designed to be used in stakeholder and public engagement events to raise awareness 350 of flood risk in the sponge city districts, and the additional identification of local issues associated with low 351 impact development and sponge city construction. The workshop includes visualization tools set up, sponge

- 352 city planning scenarios in VR, participants preferences and comments, and stakeholder analysis which is similar 353 to other knowledge exchange activities [12][43]. The model is navigable, with interactivity to appeal across the 354 range of prospective audiences. Drop-in interactive sessions of 30 minutes are planned to run throughout each 355 day, with hand-held consoles used for providing feedbacks. Presenting audiences with scenarios of potential 356 future flood mitigation measures and LID plans provides a basis for talking through opportunities, conflicts and 357 the identification of new ideas for sponge city construction. Each session comprises: 358 i) Visual exploration of flood simulation and LID scenarios from different viewpoints 359 ii) Testing, audience understanding of key messages conveyed during the sessions.
- 360 iii) Interactive exploration and voting on options for addressing local sponge city issues

361 5. Results

362 5.1 2D Simulation results with design rainstorm

Inundation maps show the combined effects of design rainstorm with different implementations of the LID approach as defined by varying input parameters. Comparing flood simulation without LID and with LID from the return periods of both 10 years (Fig.8) and 50 years (Fig.9), shows the considerable 'sponge' effect of the LID reconstruction for Xixian New District by reducing surface water flooding in the urban environments, especially for the more extreme (1 in 50 year) event.



368 369

t=1h, without LID t=1h, LID
 Fig.8. Flood inundation map with the return period of 10 years in Fengxi new town



t=2h, without LID t=2h, LID
Fig.9. Flood inundation map with the return period of 50 years in Fengxi new town

375 5.2 Flood simulation and LID scenarios in VR

A prototype VR model provides the user with overlaid data relevant to the viewer's location and field of view. In addition, an online model is used to display 3D environment integrated with spatial analysis data and other water data. This online model also serves to capture user/stakeholder comments that they associate with surface water or water retention/infiltration features and therefore to facilitate collaborative interaction based upon the design simulation results for Fengxi new town VR model.

- 381 Extra elements have been added according to participants requirements (trees, cars, characters, etc.).
- 382 Fig.10 and Fig.11 show the Fengxi new town VR model with simulated flood events before and after LID with
- 383 10-year and 50-year return period.



384

371

Fig.10. Visualize flood events in 3D virtual Environments in Qinhuang Avenue of Fengxi new town with
 10-year return period: (a) t=1h, without LID; (b) t=1h, LID.



- 387
- 388 389

Fig.11. Visualize flood events in 3D virtual Environments in Fengjing Road of Fengxi new town with 50-year return period: (a) t=2h, without LID; (b): t=2h, LID.

In Fig.12, the LID scenarios of Fengxi new town in VR model are presented. In addition to the roadside vegetation, the associated buildings with greenroof for intercepting rainwater and helping to mitigating the urban heat island effect are visible. There is a close view of 3D model of rain garden and permeable pavement in Fig.12b. Underground pipe corridors implemented in LID approach (Fig.13a) illustrate how pipe design planning not only eliminates problems of various cables in the air but also improves urban landscape, intensively utilizes urban underground space.



- 397
- 398 Fig.12. Fengxi new town LID scenarios in VR: (a) Green roof; (b) Rain Garden and Permeable Pavement
- 399 With the aid of the 360-panorama functionality of VR model, users are able to access all 360° of the
- 400 viewscape of the LID scenarios with panoramic images and interactive virtual view. In order to facilitate
- 401 immersive view, VR headset devices (Fig.13 (b)) are used to test audience perceptions and reactions.



Fig.13. (a) Fengxi new town underground pipe corridors design in VR; (b) Immersive display simulated flood event in Fengxi new town with Oculus Rift

406 For effective stakeholder engagement, it is important to provide sufficient detail of features to enable

407 participants to be able to identify and locate themselves with respect to a planned development. The level of

- 408 detail (e.g. number of features, and the visual detail with which they are presented) has been tested in a
- 409 workshop with key stakeholders (e.g. sponge city planners) and representative members of the public (e.g.
- 410 local communities public).
- 411 The responses to the proposed questions are listed in Table 4:
- 412 **Table 4** Participant preference for integrated simulation and 3D visualization in sponge city construction

Question	Yes	No	Neutral
Is 3D visualization most suitable for improving the communication and consultation process within the sponge city development?	15	5	0
Do you think 3D visualization is better for showing LID scenarios rather than 2D visualization?	16	3	1
Do you think integrated simulation and 3D visualization is more suitable for decision -making support of flood risk management in sponge city?	18	1	1

413

The preference rating for decision-making support of flood risk management is very high because the visualization of flood propagation and simulation of areas of surface water accumulation is considered practical and beneficial in terms of making effective response plans and providing detailed visual evidence.

417 Audience feedback suggested that the virtual environment was very effective in providing a more 418 realistic impression of the different layouts and characteristics of the LID approach in sponge city 419 construction, as compared to conventional 2D planning images, and that they enabled comparisons to be made 420 of the differences in the expected outcomes of the alternative simulated flood events. This suggests 421 considerable added value from using the 3D visualization to communicate the relationship between LID 422 design features and the resultant reduction in risk in the context of participatory spatial planning.

423

424 6. Discussion and Conclusion

425 In this paper, actual and design flood events in pilot sponge city have been simulated and integrated with a

426 3D VR environment. In addition, urban development scenarios have been applied into sponge city construction

18 of 22

427 using design plan both with and without LID in VR.

428 The integrated simulation and visualization platform has provided a procedure for constructing realistic 429 urban environments that incorporate flood design features and monitoring of their performance during extreme 430 rainfall events. Through the flood simulation model, it is possible to predict where the flood may have occurred, 431 how serious it would be, and how different mitigation measures may affect flood risk in different situations. The 432 simulation model can also identify areas of surface water accumulation and their hydraulic relationship to the 433 dynamics of different rainfall return period events. This includes the effects on urban stormwater processes both 434 before and after LID is carried out which is especially useful for decision makers to help identify the most 435 effective features of LID design in reducing surface runoff.

436 3D visualization was integrated at different stages throughout the process of sponge city planning which 437 includes scenarios of LID design, flood risk, vegetation creation and integrated pipe systems. For LID design, 438 the visualization is able to provide an interactive 3D model of rain gardens and permeable pavement at different 439 scales which can be shared with individuals and in collaborative groups to enable feedback through online 440 comments. Woodland creation in sponge city is presented by adjusting woodland area, mixing tree species and 441 changing tree density through 3D virtual environment in order to choose the best woodland planning scenario. 442 Our 3D flood risk model offers not only numerical data or graphical output, but has been identified from user 443 feedback to also provide more useful and appealing 3D visual information. It can handle dynamic flood 444 behaviour and predict inundation areas in real time which is important for flood warning and for disaster risk 445 planning scenarios. 3D reconstruction of underground pipelines has been implemented to help understand their 446 role in implementing an integrated spatial design relative to surface features, which is not easily apparent in 2D 447 media. This also provides effective technical support for the planning and construction of underground 448 pipelines, integration of pipe corridors into sponge cities, rational use of underground space, and safeguarding 449 of pipelines. With the help of interactive 3D visualization tools, the extent of flooding combined with other 450 features such as co-benefits of the design can be better viewed and understood, as also assisted by 360° VR 451 panorama, by which users can access a 'bird's eye' interactive view of sponge city development plan.

Results are being used to inform the design of tools for eliciting stakeholders and public responses to prospective changes in flood risk management in urban and peri-urban environments, including development of LID scenarios and flood events visualization. The enhancement of user interaction through VR has potential implications for the planning and design of sponge city to increase the effectiveness of their use, and contribution to wider green infrastructure. Community recognition of potential multiple benefits from LID in sponge city such as improving urban drainage system and reducing urban waterlogging, supports the aims of the 458 sponge city policy in respect of building ecologically-based drainage facilities, decreasing urban runoff459 pollution and protecting urban ecological environment.

The importance of adapting design concepts to local conditions is a key premise of sponge city planning and a crucial step in developing quantitative analysis in terms of scheme performance and resilience during extreme rainfall events. Our work in the pilot study areas suggests there are further steps that should also be considered in advancing integrated simulation-visualization platform:

464 (i) In order to improve the prediction accuracy of the urban flood simulation, high-resolution terrain data, as465 obtained by UAV, should be sought.

(ii) The further integration of building information modeling (BIM) and GIS applications in urban planning
should be promoted, such as through municipal pipe network management, underground integrated pipe design,
residential community planning, existing building renovation, operation and maintenance management, etc.
Combined data can be used to improve modeling accuracy, analysis accuracy, decision efficiency, and cost
control.

(iii) In addition to user interaction through a dedicated VR platform, the development of software for use with mobile devices (e.g. phones, laptop computers and tablets) appears likely to continue, exploiting increased computational capabilities of hardware and communications networks in flood risk management. An extension of Apps on mobile devices is the use of low-cost Virtual Reality headsets. These are likely to be used increasingly for early engagement with stakeholders for discussion about plans for sponge city construction in Xixian new area or eliciting ideas for potential LID scenarios.

(iv) An additional feature of the integrated simulation-visualization approach is that it can facilitate a cross-scale approach by zooming between local neighbourhood district detail and city-level planning. The requirement to integrate between scales has been recognized as a key deficiency in current sponge city design implementations[9], and further development of visualization level-of-detail implementations at different scales could be used to help address this issue.

Existing and planned future developments show there are good prospects for using interactive sponge city models to integrate georeferenced monitoring data from multiple sources through the use of combined GIS-VR platforms, which can also provide a crucial collaborative step in converting planning documents into a practical reality. In this way, interactive visualization becomes the key step in refining the initial design concept for the sponge city into a shared learning experience through which flood risk management can be better integrated with the wider range of issues that influence urban wellbeing.

489 Acknowledgments

- 490 This research was supported by the open fund grant from State Key Laboratory of Eco-hydraulics in
- 491 Northwest Arid Region, Xi'an University of Technology (Grant No. 104-206071712); Scottish Government
- 492 RESAS Research Programme; National Key Research and Development Program of China (Grant No.
- 493 2016YFC0402704); National Natural Science Foundation of China (Grant No. 19672016) and Research
- 494 Program of Sponge City at Xixian New Area, China (Grant No. 104/441216042).
- 495 References
- 496 [1]. Nguyen, T.T.; Ngo, H.H.; Guo, W.; Wang, X.C.; Ren, N.; Li, G.; Ding, J.; Liang, H. Implementation of a specific urban water 497 management-Sponge City. Science of the Total Environment. 2019, 652, 147-162.
- 498 [2]. Tredway J and Havlick D, Assessing the Potential of Low-Impact Development Techniques on Runoff and Streamflow in the 499 Templeton Gap Watershed, The Professional Geographer, 2017 - Taylor & Francis.
- 500 [3]. Lottering, N.; du Plessis, D.; Donaldson, R. Coping with drought: the experience of water sensitive urban design (WSUD) in the 501 George Municipality. Water SA 2015, 41, 1-7.
- 502 [4]. Perales-Momparler, S.; Hernández-Crespo, C.; Vallés Morán, F.; Martín, M.; Andrés-Doménech, I.; Andreu Álvarez, J.; Jefferies, C.
- 503 SuDS Efficiency during the Start-Up Period under Mediterranean Climatic Conditions. Acta Hydrochim. Hydrobiol. 2014, 42, 504 178-186.
- 505 [5]. Haghighatafshar, S., Jansen, J.L, Aspegren H, Lidström V, Mattsson A and Jönsson A, Storm-water management in malmö and 506 Copenhagen with regard to climate change scenarios. Vatten: Journal of Water Management and Research 70: 159-168, Lund 2014.
- 507 [6]. Mguni, P., Herslund L and Jensen M.B. Green infrastructure for flood-risk management in Dar es Salaam and Copenhagen: 508 exploring the potential for transitions towards sustainable urban water management. Water Policy 17(2015): 126-142, 2015.
- 509 [7]. Li, H; Ding, L.Q.; Ren, M.L.; Li, C.Z.; Wang, H. Sponge City construction in China: A survey of the challenges and opportunities. 510 Water 2017, 9, 594.
- 511 [8]. Whelchel, A. W., Renaud, F.G., Sudmeier-Rieux, K. and Sebesvari, Z. (2018) Advancing ecosystems and disaster risk 512 reduction in policy, planning, implementation, and management. International Journal of Disaster Risk Reduction, 32, pp. 513

29-41. (doi:10.1016/j.ijdrr.2018.08.008)

- 514 [9]. Zevenbergen, C.; Fu, D.; Pathirana, A. Transitioning to Sponge Cities: Challenges and Opportunities to Address Urban Water 515 Problems in China. Water 2018, 10, 1230.
- 516 [10]. Li, Z.; Xu, S and Yao, L. A Systematic Literature Mining of Sponge City: Trends, Foci and Challenges Standing Ahead, 517 Sustainability 2018, 10(4), 1182; doi:10.3390/su10041182
- 518 [11]. Portman, M.E., Natapov, A. and Fisher-Gewirtzman, D. To go where no man has gone before: Virtual reality in architecture, 519 landscape architecture and environmental planning. Computers, Environment and Urban Systems, 54, pp.376-384, 2015.
- 520 [12]. Wang, C., Miller, D.R., Brown I., Jiang Y., Castellazzi M, "Visualisation Techniques to Support Public Interpretation of Future
- 521 Climate Change and Land Use Choices: A Case Study from N-E Scotland", International Journal of Digital Earth, Volume 9, Issue 522 6, pp.586-605, 2016.
- 523 [13]. Thorne, C.R., Lawson, E.C., Ozawa, C., Hamlin, S.L., Smith, L.A. Overcoming uncertainty and barriers to adoption of Blue-Green 524 Infrastructure for urban flood risk management. J. Flood Risk Management, 2015.

- 525 [14]. Glaas, E; Hjerpe, M; Storbjörk, S; Neset, TS; Bohman, A; Muthumanickam,P; Johansson,J; Developing transformative capacity
 526 through systematic assessments and visualization of urban climate transitions. AMBIO A Journal of the Human Environment, 2018
 527 DOI: 10.1007/s13280-018-1109-9
- 528 [15]. Boughton. W and Droop. O, Continuous simulation for design flood estimation--a review. Environmental Modelling & Software,
 529 18(4): 309-318.2003.
- [16]. Mark. O, Weesakul. S, Apirumanekul. C, Aroonnet. S.B and Djordjevic. S, Potential and limitations of 1D modelling of urban
 flooding. Journal of Hydrology, 284-299, 2004.
- 532 [17]. Mignot, E, Paquier, A and Haider, S, "Modeling floods in a dense urban area using 2D shallow water equations", Journal of
- 533 Hydrology, 327 (1–2), pp. 186–199, 2006.
- 534 [18]. Marks K and Bates P, Integration of high-resolution topographic data with floodplain flow models. Hydrol Process 14:
 535 2109–22,2000.
- England JF Jr, Velleux ML, Julien PY. 2007, "Two-dimensional simulations of extreme floods on a large watershed", Journal of
 Hydrology 347(1-2): 229-241, DOI: 10.1016/j.jhydrol. 09.034, 2007.
- Franci F, Bitelli G, Mandanici E, Hadjimitsis D, Agapiou A, Satellite remote sensing and GIS-based multi-criteria analysis for flood
 hazard mapping., Natural Hazards 83:31–51, 2016
- 540 [21]. Kwak, Y.-J. Nationwide flood monitoring for disaster risk reduction using multiple satellite data. ISPRS International Journal of
 541 Geo-Information. 6(7), 203, 2017
- 542 [22]. Kay AL, Reynard NS, and Jones RG, "RCM rainfall for UK flood frequency estimation. I. Method and validation", Journal of
 543 Hydrology, Elsevier, 318 (2006) 151–162, 2006.
- 544 [23]. Chen J, Hill A and Urbano L. "A GIS-based model for urban flood inundation", Journal of Hydrology, 373, 2009, pp. 184-192.
- 545 [24]. Uddin, K.; Gurung, D. R.; Amarnath, Giriraj; Shrestha, B. 2013. Application of remote sensing and GIS for flood hazard
- 546 management: a case study from Sindh Province, Pakistan. American Journal of Geographic Information System, 2(1):1-5.
- 547 [25]. Li X Y, Chaub K.W, Cheng Chun-Tian, Li Y.S, "A Web-based flood forecasting system for Shuangpai region", Advances in
 548 Engineering Software, Elsevier, 37 (2006) 146–158,2006.
- 549 [26]. Sanyal, J., Carbonneau, P. and Densmore, A.L., 2013. Hydraulic routing of extreme floods in a large ungauged river and the
 550 estimation of associated uncertainties: a case study of the Damodar River, India. Natural hazards, 66(2), pp.1153-1177.
- [27]. Kwabena O. Asante, Rodrigues D. Macuacua, Guleid A. Artan, Ronald W. Lietzow, and James P. Verdin, "Developing a Flood
 Monitoring System From Remotely Sensed Data for the Limpopo Basin", IEEE TRANSACTIONS ON GEOSCIENCE AND
 REMOTE SENSING, VOL. 45, NO. 6, JUNE 2007.
- 554 [28]. David C. Mason, Rainer Speck, Bernard Devereux et al, "Flood Detection in Urban Areas Using TerraSAR-X", IEEE
- 555 TRANSACTIONS ON GEOSCIENCE AND REMOTE SENSING, VOL. 48, NO. 2, FEBRUARY 2010
- 556 [29]. De Roo APJ, Barrthholmes J, Bongioannini-Cerlini P, Todini E, Bates PD, Horrit M, Hunter N, Beven K, Pappenberger F, Heise E,
- 557 Rivin G, Hils M, Hollingsworth A, Holst B, Kwadijk J, Reggiance P, VanDijk M, Sattler K, Sprokkereef E. 2003. Development of a
- 558 European flood forecasting system. Int. J. River Basin Management 1: 49–59.
- [30]. Rehman, S., Sahana, M., Hong, H., Sajjad, H. and Ahmed, B.B., 2019. A systematic review on approaches and methods used for
 flood vulnerability assessment: framework for future research. Natural Hazards, pp.1-24.
- 561 [31]. Takabatake T, Shibayama T, Esteban M, Ishii H, Hamano G, Simulated tsunami evacuation behaviour of local residents and visitors
- 562 in Kamakura, Japan, International Journal of Disaster Risk Reduction, 23, pp 1-14, 2017

- 563 [32]. Nga, P.H.; Takara, K.; Van, N.C. Integrated approach to analyze the total flood risk for agriculture: The significance of intangible
- damages—A case study in Central Vietnam. International Journal of Disaster Risk Reduction. 2018, 31, 862–872
- [33]. Leedal D, Neal J, Beven K, Young P, Bates P (2010) Visualization approaches for communicating real-time flood forecasting level
 and inundation information. Journal of Flood Risk Management, Volume 3 Issue 2 pp 140-150,2010.
- 567 [34]. Azam, M.; Kim, H.S.; Maeng, S.J. Development of flood alert application in Mushim stream watershed Korea. International Journal
 568 of Disaster Risk Reduction. 2017, 21, 11–26.
- 569 [35]. http://en.xixianxinqu.gov.cn/
- 570 [36]. Hou J, Liang Q, Zhang H, et al. An efficient unstructured MUSCL scheme for solving the 2D shallow water equations,
- 571 Environmental Modelling & Software, 2015, 66: 131–152.
- 572 [37]. Toro, E. F.; Spruce, M.; Speares, W., "Restoration of the contact surface in the HLL-Riemann solver", Shock Waves, 4 (1): 573 25–34,1994.
- 574 [38]. Hou J, Simons F, Mahgoub M, et al. A robust well-balanced model on unstructured grids for shallow water flows with wetting and
- 575 drying over complex topography, Computer Methods in Applied Mechanics & Engineering, 2013, 257(15): 126–149.
- 576 [39]. Hou J., Wang T. Li P, et al. An Implicit Friction Source Term Treatment for Overland Flow Simulation Using Shallow Water Flow
 577 Model, Journal of Hydrology, 2018, 564: 357–366.
- [40]. Hou J, Özgen I. A model for overland flow and associated processes within the Hydroinformatics Modelling System, Journal of
 Hydroinformatics, 2014, 16(2): 375–391.
- 580 [41]. Hou J, Guo K, Liu F. Designing Storm Formula and Pattern in Fengxi New City, Xixian New Area, 2018 (in Chinese).
- 581 [42]. Gao E P. Research on manning coefficient of different vegetated slope, Beijing: Beijing Forestry University, 2014.
- 582 [43]. Leskens, Johannes G., Christian Kehl, Tim Tutenel, Timothy Kol, Gerwin de Haan, Guus Stelling, and Elmar Eisemann. "An
- Interactive Simulation and Visualization Tool for Flood Analysis Usable for Practitioners." Mitigation and Adaptation Strategies for
 Global Change 1-18, 2015.
- 585